

LINK AGUGLIATO DI VETRO LINK NEEDLED GLASS MAT

Link agugliato di vetro è un feltro in fibra di vetro per l'isolamento termico e acustico.
Link needled glass mat is a glass fiber mat for thermal and acoustic insulation.

Caratteristiche tecniche / Technical characteristics

CARATTERISTICHE / CHARACTERISTIC	VALORE / VALUE
• Densità nominale / Nominal Density	120-200 kg/m ³
• Diametro fibre / Filament diameter	3 - 25mm
• Spessore / Thickness	1000mm
• Altezza standard / Standard height roll	550°C
• Temperatura in continuo / Continuous temperature	675°C
• Temperatura di picco / Peak temperature	Incombustibile / Fire resistant
• Comportamento al fuoco / Response to fire	Nessuna / None
• Emissione fumi / Fume emission	

Conducibilità termica per materasso 130kg/m³ Thermal conductivity for mat 130kg/m³

Temp °C	100	200	300	400	500
W/m ² K	0,039	0,052	0,067	0,085	0,108

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product. This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Rev. 1 of 21/06/2017